

## Heating Expansion Vessel c/w kit

Model: IB050PACK

Size: 50 Ltr

- Maximum working pressure 4 bar
- Pre-charge 1.5 bar
- Temperature range - 10 °C + 100 °C
- Dimensions D 360 x 630 Height
- Water Connection 3/4"
- Weight 7.5 Kilos
- High resistant rubber bladder
- Floor mounted – no bracket required

**Components:** 50 Ltr heating vessel  
Brass Cross Manifold  
Mounting Bracket  
1/2" Safety Relief Valve 3 bar c/w gauge  
15mm Combi filling loop



**Approvals:** - (Vessel) CE endorsed, TUV

The central heating system most commonly used in Europe and other parts of the world is a sealed system. Ease of installation makes it particularly attractive to the installer, as a sealed system alleviates the need to fit, feed and vent tanks in the central heating system.

- **System flexibility** - due to component siting alternatives
- **cost savings** - due to considerably reduced installation time
- **no feed and expansion tank** - hence avoiding 'pumping over' problems, risk of freezing up etc.
- **longer life** - due to virtual elimination of corrosion problems
- **noise reduction** - due to higher system pressure, boiler noise (localised heating) is significantly reduced or eliminated
- **low maintenance cost** - as equipment is virtually maintenance free, other than for periodic operational checks
- **water supply** (water regulations) G.24.1 and 24.2 compliant filling loop 10