

Inta Deluge Optimo – Shower valve with telescopic fixed riser and adjustable bar

The Inta range of showers has been designed to give you the best of both worlds. The Inta collection offers the ultimate balance between excellent performance and the latest designs to suit every bathroom.



- Bar type shower valve with independent control of temperature and flow
- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Thermal Cartridge technology
- Temperature stability of +/-2°C
- Fail safe on hot and cold supplies
- Operating pressure range of 0.1 to 5 bar
- Available in Chrome
- Telescopic fixed riser
- Integrated fixed riser and handset shower kit

Approvals: TMV2

Max Inlet pressure static:	5 Bar
Min Inlet pressure:	0.4 Bar
Max Inlet Temperature:	85 °C
Factory Pre-set temperature:	38 °C with max temp stop
Inlet Connections:	G ½" F BSP (valve only)
Outlet Connections:	G ½" F BSP
Min. Temperature to achieve hot or cold failsafe:	15 °C
System installation:	Unvented, Pressurised,
Gravity and Combination boilers.	

Performance:

Open outlet at 43 °C

Pressure drop (bars)	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9	1.0
(L/min)	4.5	5.5	7.5	8.5	9.0	9.5	10	10.5	11	11.5