

## Intamix Pro V Thermostatic Mixing Valve

Model: IN61028CP

Connection: 28mm cu x cu x cu x cu c/w check valves

### Materials:

**Body:** DZR Brass  
**Cartridge:** DZR Brass  
**Shutter:** DZR Brass  
**Spring:** Stainless Steel  
**Seal components:** EPDM

### Temperatures and pressures:

Outlet Temperature range settings: 30 – 65 °C  
Minimum flow rate to ensure stable temp: 0.083l/s – 5l/m  
Accuracy:  $\pm 2$  °C  
Max. working pressure: 14 bar – static  
5 bar – dynamic  
Max. inlet temperature: 85 °C  
Max. inlet pressure ration (H/C or C/H) 2:1

- Tamperproof head
- Single piece thermostatic cartridge construction
- High Flow rate
- Adjustable Outlet temperature
- Accessories available
- Automatic shut off in the event of hot or cold water failure
- Temp. stability  $\pm 2$  °C

### Function:

The Intamix Pro is designed for use in applications where a high volume of water is required at the outlet such as shower blocks and centralised mixing. Providing a high volume of water at a stable temperature the IntaMix Pro reflects the quality of the Intatec range of total washroom solutions.

**Approvals:** WRAS and TMV2

