

Inta Inta Minimalistic Shower System

Intaflo shower products have been independently tested and certified by the WRC Testing & Evaluation Centre and meets the requirements of both TMV3 / MES D08 / BS 7942, and TMV2 / BS EN 111 & BS EN 1287.

In layman's terms, this simply means that the products are thermostatically controlled and provide anti-scald protection for users.

Normally with such highly certified and technical products, you'd expect there to be a design trade-off. But not with the Intaflo range. We've managed to achieve the ultimate balance of excellent performance and stunning design. The very distinctive product mix includes traditional, modern and minimalist styles finished in chrome. There's also the option of concealed or exposed valves to bring any bathroom up to date simply and effectively.

Modern

The Intatec range of Modern shower valves is the simple way to bring your bath or shower room up to date. The Modern range of showers from Intatec brings style, performance and whether concealed or exposed, the Modern valve is an easy and classic way to update the bathroom.

Max Inlet Pressure:	10 Bar
Min Inlet Temperature:	0.1 Bar
Max Inlet Temperature:	85 °C
Factory Preset Temperature:	43 °C
Inlet Connections:	15mm
Outlet connections:	2 x ½" BSP
Min Temperature to achieve hot or cold failsafe:	10 °C

Approvals: WRAS TMV2 and TMV3

- Dual control shower valve for independent control of temperature and flow
- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Single piece thermal cartridge technology
- Factory set at 43 °C to prevent scalding
- Temperature stability of ± 2 °C
- Failsafe on hot and cold supplies
- Operating pressure range of 0.1 to 10 bar
- WRAS approved
- TMV2 and TMV3 approved
- Also available in exposed model
- c/w riser rail with 2 metre hose and handset.

