

Counter Top Stainless Steel Range Of Water Boilers

Model: CT6000-6

Electrical power loading: 6 Kw

Designed for situations where large volumes are needed over a short period of time.

- Programmable seven day timer
- Stylish, compact, reliable and long lasting
- Energy saving ECO mode on all models
- Electronically controlled for constant temperatures programmable between 80 °C and 98 °C
- Large non-drip tap
- Easy installation and maintenance
- Insulated for economy and safety
- Low voltage switching on all controls
- Stainless steel casing
- Minimal steam escape
- Early warning intelligent diagnostics with LCD read out
- Five water level sensors
- Safety cut out on overflow and element
- Choice of overflow position to front or rear
- Stainless steel drip tray included
- Drip tray included
- Basic fault self diagnosis with clear LCD read out
- 2 years on site parts and labour guarantee
- 2 metre food quality hose with ¾" BSP connections

Heat up time from cold in minutes:	41
Rapid draw off in litres when full:	33
Rapid draw off in cups * when full:	198
Hourly output litres:	57
Hourly Output cups *:	342
Recovery per minute in litres:	1
Electrical power loading:	6 Kw
Standby power consumption in KW/hour:	0.17

Dimension:	H 608mm
	W 440mm
	D 555mm
Tap clearance:	165mm
(Allow up to 45mm on depth for connection to rear).	

Approvals: WRAS and Kiwa

