

## Inta HTM64 Hospital Fittings (TBH 2a) \*

The HTM thermostatic hospital fitting is purposely designed for use in hospitals, healthcare and commercial applications. The long sequential lever rotates smoothly through 180 oC and can be operated easily by either the wrist or elbows. Making it ideal for use scrub up areas, consulting rooms, Doctors surgeries and anywhere that hygiene is paramount.



- In line isolating ball valves
- Simple operation
- TMV3 approved
- WRAs approved
- Complies with HTM64 type TB H2a
- Highly polished Chrome
- Easy to grip
- Available with deck mounts and extended legs

### Approvals: TMV3 & WRAS

Max Dynamic pressure:	5 Bar
Max Static pressure:	12 Bar
Max Operating pressure:	0.2 Bar
Max Inlet Temperature:	85 °C
Min Inlet Temperature:	10 °C
Temperature stability:	± 2_ °C
Min. Temperature differential to ensure for failsafe between hot and cold supplies:	10 °C
Max unbalanced pressure ratio (with flow regulators)	15:1
Max unbalanced pressure ratio (without flow regulators)	5:1
DOE working pressure ranges (low pressure)	0.2 – 1 bar
DO8 working pressure ranges (high pressure)	1 – 5 bar

\*

HTM64 Code	HTM64 Description	Code
TB H2a	Hospital pattern integral thermostatic bib mixer tap	INHTM09025CP
TB H6	Hospital pattern integral thermostatic bib mixer tap proximity sensor, timed flow	INHTM09031CP
TP6	General basin ½" thermostatic mixer tap	INIT1001CP/IT1003CP
TPP1	General basin ½" self closing mixer	INNC230CP
TM1	Thermostatic shower mixer, flexible hose and handset	IN90032CP/INLA014CP