

Zip Aquapoint III Unvented Water Heater - OVERSINK

Single or multiple outlet water heater.

Capacity: 5 Ltrs

Rating: 2 Kw

Water Tank: Hot water storage tank of 1.8mm thick glass enamelled steel tested to 12 bar

Case: High impact and corrosion resistant white plastic

Insulation: High Density CFC-free polyurethane foam insulation

Safety features: Resettable over temperature safety cut out.

- a. Manually resettable thermal cutout set to 85 °C +/- 3 °C
- b. expansion relief valve (supplied) set at 6 bar.
- c. protected against frost whilst power is on.
- d. sacrificial anode for added protection against corrosion for element and tank – must be checked regularly (6 months) and replaced where necessary as gradual erosion will occur.

In extreme cases local water conditions can cause rapid erosion of the anode resulting in particles being deposited as a residue.

Taps: No special taps required.

Approvals: WRAS approved and CE endorsed.

Dimensions: H 376 x W 256 x D 260

Weight (kg)	Empty	Full
	6.7	12.7

Plumbing: Water connection 15mm BSP

Electrical: To be wired to a double pole fused spur, minimum break rating of 13 amp.

Minimum recommended water pressure 1 bar

Pressure and temperature relief valve, where fitted requires plumbing to waste in accordance with water byelaws.

Minimum length of pipe (from water heater to nearest draw off tap)

For a 10 Ltr Unit using 15mm pipe work: 2.7 metres (9ft)
 " 22mm pipe work: 1.2 metres (4ft)

If you do not have this minimum length of pipe work then you will need to fit Pack AQ2.

Minimum length of pipe (from water heater to nearest draw off tap)

For a 5 Ltr Unit using 15mm pipe work: 1.2 metres (4ft)
 " 22mm pipe work 0.6 metres (2ft)

If you do not have this minimum length of pipe work then you will need to fit Pack AQ2.

Warranty: 12 months.

Performance

Model	Heat up time to 15 °C	Re-heat time to (70% vol)
AP3/05	11 mins	7 mins
AP/310	18 mins	12 mins
AP/315	32 mins	18 mins

