

Zip Aquapoint III Unvented Water Heater - UNDERSINK

Single or multiple outlet water heater.

Capacity: 100 Ltrs

Rating: 3 Kw

Water Tank: Hot water storage tank of 1.8mm thick glass enamelled steel tested to 13 bar. 3kw.

Case: High impact and corrosion resistant white plastic

Insulation: High Density CFC-free polyurethane foam insulation

Safety features: Resettable over temperature safety cut out.

- a. Manually resettable thermal cutout set to 85 °C +/- 3 °C
- b. expansion relief valve (supplied) set at 6 bar.
- c. protected against frost whilst power is on.
- d. sacrificial anode for added protection against corrosion for element and tank – must be checked regularly (6 months) and replaced where necessary as gradual erosion will occur.

In extreme cases local water conditions can cause rapid erosion of the anode resulting in particles being deposited as a residue.

Taps: No special taps required.

Approvals: WRAS approved and CE endorsed.

Dimensions: H 1125 x W 420 x D 445

| Weight (kg) | Empty | Full |
|-------------|-------|------|
| | 24 | 74 |

Plumbing: Water connection 15mm BSP

Minimum recommended water pressure 1 bar

Pressure and temperature relief valve, where fitted requires plumbing to waste in accordance with water byelaws.

Electrical: To be wired to a double pole fused spur, minimum break rating of 13 amp.

Warranty: 12 months.

Performance

| Model | Heat up time to 15 °C to 65 °C | Re-heat time to (70% vol) |
|--------|--------------------------------|---------------------------|
| AP3/30 | 37 mins | 23 mins |
| AP/350 | 58 mins | 38 mins |
| AP/380 | 88 mins | 58 mins |
| AP/310 | 110 mins | 72 mins |

