

Zip Aquapoint

This unvented water heater range comes in a variety of capacities and offers over-sink or under-sink installation. Suitable for single or multiple outlets, Aquapoint III is glass-lined and features external temperature control and frost protection.



MODEL	ENERGY EFFICIENCY CLASS (ERP)	DIMENSIONS W X D X H	NOMINAL POWER RATING KW	RE-HEAT TIME (HH:MM)	CAPACITY (LITRES)
AP3/15/OB	A	350mm x 310mm x 480mm	2 kW @ 230V	00:29	14.9

Features and benefits

Glass lined steel inner container

Tested to 13 bar

Sacrificial anode

For protection against corrosion

Approvals

WRAS approval and CE endorsed

Insulation

High performance foam

External temperature control

Can be replaced without draining

Product detail

Specification type

Product code	AP3/15/OB
Product name	Aquapoint III Unvented 15 Litre Overbasin
Energy Efficiency Class	A
WRAS Approval	Yes
Wras Number	1411062

Capacity, weights & dimensions

Capacity (Litres)	14.9 L
Unit dimensions (W x D x H) mm	350 x 310 x 480
Empty weight	9.8kg
Filled weight	24.7kg

Electrical

Nominal power rating	2 kW @ 230V
Nominal power supply	230V
Nominal rated current	8.7 amps
IP rating	24

Plumbing

Wholesome water supply	Yes
Wholesome connection size	1/2"bsp
Minimum supply water pressure	0.1bar
Maximum supply water pressure	5.5bar



The Zip Aquapoint III must be installed in accordance with the installation instructions and all current legislation, codes of practice and regulations governing the installation of unvented hot water cylinders in force at the time of installation. The appliance must be permanently connected to the supply through an isolating switch with a contact separation of at least 3mm in all poles and be protected by a suitably rated RCD to protect the appliance, an MCB (miniature circuit breaker) or fuse must be fitted with a rating suitable for the nominal current of the appliance.